


## Gerader Verbinder straight connector



<b>Betriebstemperatur</b>	-20°C bis +70°C	<b>operating temperature</b>	-20°C up to +70°C
<b>Betriebsdruck</b>	max. 16bar	<b>operating pressure</b>	max. 16bar
<b>Werkstoff</b>	Gehäuse Messing (Ms58) vernickelt Dichtung aus NBR silikonfrei Spannzange aus Edelstahl 1.4404 Druckring aus Kunststoff schwarz	<b>material</b>	body brass (Ms58) nickel-plated silicon-free NBR seals stainless steel clamp 1.4404 black plastic thrust ring

ØD1 [mm]	ØD2 [mm]	ØB1 [mm]	ØB2 [mm]	ØC [mm]	L [mm]
3,0	3,0	6,5	6,5	2,0	21,0
4,0	4,0	9,0	9,0	3,0	31,0
5,0	5,0	9,5	9,5	4,0	33,0
6,0	6,0	11,0	11,0	5,0	33,0
8,0	8,0	13,0	13,0	7,0	37,0
10,0	10,0	15,0	15,0	9,0	39,0
12,0	12,0	17,0	17,0	11,0	43,0
14,0	14,0	20,0	20,0	12,0	47,5
<b>Reduziert / reduced</b>					
6,0	4,0	11,0	9,0	3,0	33,0
8,0	6,0	13,0	11,0	5,0	39,0
10,0	8,0	16,0	13,0	7,0	39,5
12,0	10,0	20,0	15,0	9,0	41,5
14,0	12,0	22,0	17,0	11,0	45,5

**weitere Optionen und Zubehör auf Anfrage**  
more options and accessories on request